Strainer PN 10 Y-type, with flanged ends and drain-plug 1/2”BSP in cover



Materials: Body: cast iron JL 1040, Screen: stainless steel 1.4301 (from DN 150 perforated plate 1.4301), Gasket: graphit reinforced

Connection: flanged ends DIN

Test pressure: 15 bar

Specials: with connection for differential gauge in body DN 15 - DN 40 G 1/4" and DN 50 - DN 250 G 1/2".Valves made of cast iron are not authorized for use in systems subject TRD110.

DN	L	A	Mesh-width*	Weight (kg)	Article No.**
200	600	360	1,20	99,50	96010200GLT


* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%
** When ordering with fine screen: Article-Nr. + addition "with F-SIEB"

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	ø G	ø R	P	D	B
200	360	208	36 %	820,00	769,00	3,81	4,33	240	209	2,0	Ø 290	580

The delivery of the strainer is in accordance to PED 2014/68/EU Point 11 and 12 of the preamble and article 1, clause c as well as article 4, clause 3.
The picture shown is only a symbolic photo! Subject to technical changes and errors.

LUDEMANN ARMATUREN
Broichstrasse 52
D-51109 Köln
Phone +49 (0)221-93 35 34-0
Fax +49 (0)221-93 35 34-29
E-mail armaturen@ludemann.info
Web www.ludemann.info

Key for our datasheets



DN	Nominal diameter
L	Face to face dimension (mm)
A	Centre line of pipe to end of cover (mm)
L1	Screen length (mm)
D1	Screen diameter (mm)
Fo	Free screen area standard element (mm)
KVS1	KVS-Value standardscreen (m3/h)
KVS2	KVS-Value fine screen (m3/h)
Zet1	Zeta-Value standardscreen
Zet2	Zeta-Value fine screen
ø G	Outer-diameter coverflange gasket (mm)
ø R	Inner-diameter coverflange gasket (mm)
P	Thickness coverflange gasket (mm)
D	Coverflange size
B	Distance required to remove screen (mm)

LUDEMANN ARMATUREN

Broichstrasse 52
D-51109 Köln

Phone +49 (0)221-93 35 34-0
Fax +49 (0)221-93 35 34-29

E-mail armaturen@ludemann.info
Web www.ludemann.info