

Strainer PN 25/40 Y-type, with flanged ends and drain-plug 1/2" in cover



- Materials:** Body: GS-C 25, Screen: stainless steel 1.4301, Gasket: graphit reinforced
- Connection:** flanged ends DIN
- Test pressure:** 60 bar
- Specials:** with connection for differential gauge in body DN 15 - DN 40 and DN 80 G 1/4" and DN 50 - DN 250 G 1/2"

DN	L	A	Mesh-width*	Weight (kg)	Article No.**
15	130	75	0,54	2,50	20325015GLT
20	150	75	0,54	3,00	20325020GLT
25	160	90	0,87	4,00	20325025GLT
32	180	90	0,87	5,00	20325032GLT
40	200	110	0,87	7,00	20325040GLT
50	230	120	0,87	11,00	20325050GLT
65	290	140	0,87	18,00	20325065GLT
80	310	165	1,32	23,00	20325080GLT
100	350	220	1,32	31,00	20325100GLT
125	400	260	1,32	48,00	20325125GLT
150	480	300	1,32	61,00	20325150GLT
200	600	360	1,32	153,00	20340200GLT


* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition "with F-SIEB"

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	ø G	ø R	P	D	B
15	62	22,5	39 %	2,70	2,50	2,14	2,50	39	27	1,5	40x98 oval	120
20	62	22,5	39 %	8,80	7,10	2,14	2,50	39	27	1,5	40x98 oval	125
25	86	35	38 %	16,90	15,50	2,14	2,55	56	40	1,5	48x78 oval	150
32	86	35	38 %	25,00	20,60	2,58	3,87	56	40	1,5	54x89 oval	170
40	98	45	38 %	38,00	33,20	2,83	3,67	68	51	1,5	70x72	205
50	111	55	38 %	56,00	47,50	3,11	4,36	84	58	1,5	91x95	250
65	121	63	38 %	89,00	72,70	3,51	5,28	95	71	1,5	100x110	285
80	137	77	38 %	127,00	96,80	4,02	6,90	122	98	2,0	121x131	330
100	169	100	36 %	200,00	167,00	3,92	5,63	137	115	2,0	137x145	415
125	198	120	36 %	332,00	284,00	3,49	4,77	155	126	1,5	175x190	484
150	239	150	36 %	494,00	389,00	3,26	5,26	220	180	2,0	Ø 306	535
200	290	186	36 %	675,00	570,00	5,50	7,60	260	212	2,0	Ø 345	720

The delivery of the strainer is in accordance to PED 2014/68/EU Point 11 and 12 of the preamble and article 1, clause c as well as article 4, clause 3. The picture shown is only a symbolic photo! Subject to technical changes and errors.

Key for our datasheets



DN	Nominal diameter
L	Face to face dimension (mm)
A	Centre line of pipe to end of cover (mm)
L1	Screen length (mm)
D1	Screen diameter (mm)
Fo	Free screen area standard element (mm)
KVS1	KVS-Value standardscreen (m3/h)
KVS2	KVS-Value fine screen (m3/h)
Zet1	Zeta-Value standardscreen
Zet2	Zeta-Value fine screen
Ø G	Outer-diameter coverflange gasket (mm)
Ø R	Inner-diameter coverflange gasket (mm)
P	Thickness coverflange gasket (mm)
D	Coverflange size
B	Distance required to remove screen (mm)