



Strainer PN 25 Y-type, with flanged ends and drain-plug 1/2" BSP in cover

Materials: Body: cast steel GP 240GH, Screen: stainless steel 1.4301, Gasket: graphit reinforced

Connection: flanged ends DIN

Test pressure: 32,50 bar


Specials: with connection for differential gauge

DN	L	A	Mesh-width*	Weight (kg)	Article-Number**
200	600	360	1,32	153,00	20325200GLT

* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition with F-SIEB

DN	L1	D1	Fo	KVS1	KVS2	Zet1	Zet2	Ø G	Ø R	P	D	B
200	290	186	36%	675,00	570,00	5,50	7,60	260	212	2,0	Ø 345	720



Key for our datasheets

DN	Nominal diameter
L	Face to face dimension (mm)
A	Centre line of pipe to end of cover (mm)
L1	Screen length (mm)
D1	Screen diameter (mm)
Fo	Free screen area standard element (mm)
KVS1	KVS-Value standardscreen (m ³ /h)
KVS2	KVS-Value fine screen (m ³ /h)
Zet1	Zeta-Value standardscreen
Zet2	Zeta-Value fine screen
Ø G	Outer-diameter coverflange gasket (mm)
Ø R	Inner-diameter coverflange gasket (mm)
P	Thickness coverflange gasket (mm)
D	Coverflange size
B	Distance required to remove screen (mm)

The delivery of the strainer is in accordance to PED 2014/68/EU

Point 11 and 12 of the preamble and article 1, clause c as well as article 4, clause 3.

Subject to technical changes and errors.

