



Strainer PN 25 Y-type, with flanged ends and drain-plug 1/2" BSP in cover

Materials: Body: GS-C 25, Screen: stainless steel 1.4301, Gasket: graphit reinforced

Connection: flanged ends DIN

Test pressure: 32,50 bar


Specials: with magnetit seperator

| DN | L | A | Mesh-width* | Weight (kg) | Article-Number** |
|-----|-----|-----|-------------|-------------|------------------|
| 200 | 600 | 360 | 1,32 | 153,00 | 2032520003 |

* Fine screens at all nominal diameters mesh width 0,25 mm, free area 37%

** When ordering with fine screen: Article-Nr. + addition with F-SIEB

| DN | L1 | D1 | Fo | KVS1 | KVS2 | Zet1 | Zet2 | Ø G | Ø R | P | D | B |
|-----|-----|-----|-----|--------|--------|------|------|-----|-----|-----|-------|-----|
| 200 | 290 | 186 | 36% | 675,00 | 570,00 | 5,50 | 7,60 | 260 | 212 | 2,0 | Ø 345 | 720 |



Key for our datasheets

| | |
|------|--|
| DN | Nominal diameter |
| L | Face to face dimension (mm) |
| A | Centre line of pipe to end of cover (mm) |
| L1 | Screen length (mm) |
| D1 | Screen diameter (mm) |
| Fo | Free screen area standard element (mm) |
| KVS1 | KVS-Value standardscreen (m ³ /h) |
| KVS2 | KVS-Value fine screen (m ³ /h) |
| Zet1 | Zeta-Value standardscreen |
| Zet2 | Zeta-Value fine screen |
| Ø G | Outer-diameter coverflange gasket (mm) |
| Ø R | Inner-diameter coverflange gasket (mm) |
| P | Thickness coverflange gasket (mm) |
| D | Coverflange size |
| B | Distance required to remove screen (mm) |

The delivery of the strainer is in accordance to PED 2014/68/EU

Point 11 and 12 of the preamble and article 1, clause c as well as article 4, clause 3.

Subject to technical changes and errors.

